

SL215 SEALER TAG

This tag is a very effective tracking tag for managing purpose, it can be used in the management and tracking of precision machinery, equipments and facilities such as:

1. Water Meter
2. Gas meter
3. Electric meter
4. Public transportation vehicle meters, such as taxi and bus...etc.
5. Various precision machinery and equipments to prevent from non-authorized personnel to operate the said equipments.

SL215 RFID Sealer Tag Specification

| Model No. | SL215 |
|---|---------------|
| Reading Distance | 40mm |
| Base on GK4001 chip, with EM9917 reader | |
| Operating temperature | -40°C to 70°C |
| Storage temperature | -40°C to 80°C |
| Material | ABS |
| Shower proof | Y |
| Technology | |
| GK4001 (125KHz,64bit,R/O) | Y |
| EM4102 (125KHz, 64bit,R/O) | Y |
| I-Code SLI (13.56MHz,1024bit,R/W) | Y |
| Mifare S50 (13.56MHz,1KByte,R/W) | N |
| Temic E5557 (125KHz,330bit,R/W) | Y |
| Hitag 1 (125KHz,2048bit,R/W) | Y |
| Hitag 2 (125KHz,256bit,R/W) | Y |
| Legic 256 (13.56MHz,256Byte,R/W) | Y |

